

20 °C		Количество профилей i [шт.]	t <sub>1</sub> /t <sub>2</sub> [°C]	ТЕПЛОВАЯ МОЩНОСТЬ Q [Вт] СОГЛАСНО EN 442										
Тип	Высота H [мм]			Шаг подключения h [мм]	Длина L [мм]	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
						K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
				500			600			700				
				450			550			650				
				50			50			50				
Тепловая мощность Q [Вт]														
144	2	90/70	113	147	172	134	173	203	155	198	233			
		70/55	73	96	110	86	112	129	100	128	149			
		55/45	47	62	70	56	73	82	64	83	95			
218	3	90/70	171	223	261	203	262	307	235	300	353			
		70/55	110	145	166	131	170	196	151	194	225			
		55/45	71	94	106	84	110	125	97	126	143			
366	5	90/70	286	374	438	340	439	516	394	503	593			
		70/55	185	244	279	219	286	329	254	326	378			
		55/45	119	159	178	141	185	209	163	211	240			
514	7	90/70	402	526	615	478	617	725	553	706	833			
		70/55	260	342	392	308	401	462	356	458	531			
		55/45	167	223	250	198	260	294	229	297	337			
588	8	90/70	460	601	703	546	706	829	633	808	953			
		70/55	297	392	449	352	459	529	407	524	607			
		55/45	192	255	286	227	298	336	262	339	386			
662	9	90/70	518	677	792	615	795	933	713	910	1073			
		70/55	334	441	505	397	517	595	459	590	683			
		55/45	216	287	322	255	335	379	295	382	435			
884	12	90/70	691	904	1057	821	1062	1247	951	1215	1433			
		70/55	447	589	674	530	690	795	613	788	913			
		55/45	288	383	429	341	448	506	394	510	580			
958	13	90/70	749	980	1146	890	1150	1351	1031	1316	1553			
		70/55	484	638	731	574	748	861	664	854	989			
		55/45	312	415	465	370	485	548	427	553	629			

ОСНОВНЫЕ ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ									
Тип	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
Высота H [мм]	500			600			700		
Номинальная тепловая мощность Q <sub>N</sub> [W/m]	626	822	951	743	964	1121	860	1102	1288
Температурный коэффициент n [-]	1,2638	1,2399	1,2994	1,2682	1,2459	1,3015	1,2725	1,2518	1,3037

Вес и объем воды см. стр. 18.

Характеристическое уравнение :  $\Phi_L = K_L \cdot H^b \cdot \Delta T^{(c_0+c_1 \cdot H)}$

20 °C		Количество профилей i [шт.]	t <sub>1</sub> /t <sub>2</sub> [°C]	ТЕПЛОВАЯ МОЩНОСТЬ Q [Вт] СОГЛАСНО EN 442										
Тип	Высота H [мм]			Шаг подключения h [мм]	Длина L [мм]	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
						K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
				800			900			1000				
				750			850			950				
				50			50			50				
Тепловая мощность Q [Вт]														
144	2	90/70	176	222	263	197	246	293	218	270	322			
		70/55	113	144	168	127	159	186	140	174	205			
		55/45	73	93	107	81	103	118	90	112	130			
218	3	90/70	267	337	399	299	373	444	330	408	488			
		70/55	171	218	254	192	241	282	212	263	310			
		55/45	110	141	161	123	155	179	135	169	197			
366	5	90/70	448	565	669	501	626	745	555	686	819			
		70/55	288	366	426	322	404	474	355	442	521			
		55/45	185	236	271	206	261	301	227	284	330			
514	7	90/70	629	794	940	704	879	1046	779	963	1151			
		70/55	404	514	598	452	568	665	499	621	731			
		55/45	260	332	380	290	366	422	319	399	464			
588	8	90/70	720	908	1076	806	1006	1197	891	1102	1316			
		70/55	463	588	685	517	650	761	571	710	837			
		55/45	297	380	435	331	419	483	365	457	531			
662	9	90/70	810	1022	1211	907	1132	1347	1003	1240	1482			
		70/55	521	662	771	582	731	857	643	799	942			
		55/45	334	427	490	373	472	544	411	514	598			
884	12	90/70	1082	1365	1617	1211	1512	1799	1340	1656	1979			
		70/55	695	883	1029	777	977	1144	859	1068	1258			
		55/45	446	571	654	498	630	727	549	687	798			
958	13	90/70	1172	1479	1752	1312	1639	1950	1452		2145			
		70/55	754	957	1115	842	1058	1240	930		1363			
		55/45	484	619	709	540	682	787	595		865			

ОСНОВНЫЕ ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ									
Тип	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
Высота H [мм]	800			900			1000		
Номинальная тепловая мощность Q <sub>N</sub> [W/m]	977	1237	1453	1093	1369	1616	1208	1498	1777
Температурный коэффициент n [-]	1,2769	1,2578	1,3058	1,2813	1,2638	1,3079	1,2857	1,2698	1,3101

Вес и объем воды см. стр. 18.

Характеристическое уравнение :  $\Phi_L = K_L \cdot n^b \cdot \Delta T^{(c_0+c_1 \cdot H)}$

20 °C		Количество профилей i [шт.]	t <sub>1</sub> /t <sub>2</sub> [°C]	ТЕПЛОВАЯ МОЩНОСТЬ Q [Вт] СОГЛАСНО EN 442										
Тип	Высота H [мм]			Шаг подключения h [мм]	Длина L [мм]	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
						K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
						1100			1200			1400		
				1050			1150			1350				
				50			50			50				
Тепловая мощность Q [Вт]														
144	2	90/70	239	293	352	260	316	381	302	361	438			
		70/55	153	189	223	166	203	241	193	231	277			
		55/45	98	121	141	106	130	153	123	147	175			
218	3	90/70	362	444	532	394	478	576	457	546	663			
		70/55	232	285	338	252	307	365	292	349	419			
		55/45	148	183	214	161	197	231	187	223	264			
366	5	90/70	608	745	894	661	803	967	768	917	1113			
		70/55	389	479	567	423	516	613	491	587	703			
		55/45	249	308	359	270	331	388	313	375	444			
514	7	90/70	854	1046	1255	928	1128	1359	1078	1288	1563			
		70/55	547	673	797	594	724	861	689	824	988			
		55/45	350	432	505	380	464	545	440	526	623			
588	8	90/70	977	1197	1436	1062	1290	1554	1234	1474	1788			
		70/55	626	770	911	680	828	985	788	943	1130			
		55/45	400	495	577	434	531	623	503	602	713			
662	9	90/70	1100	1348	1617	1196	1453	1750	1389	1659	2013			
		70/55	704	867	1026	765	933	1109	888	1061	1272			
		55/45	451	557	650	489	598	702	566	678	803			
884	12	90/70	1469	1800	2159	1597	1940	2337	1855	2216	2688			
		70/55	941	1158	1370	1022	1245	1481	1185	1417	1699			
		55/45	602	744	868	653	798	937	756	905	1072			
958	13	90/70	1592		2339	1731		2532	2010		2913			
		70/55	1019		1485	1108		1605	1284		1841			
		55/45	652		941	708		1015	820		1162			

ОСНОВНЫЕ ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ									
Тип	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
Высота H [мм]	1100			1200			1400		
Номинальная тепловая мощность Q <sub>N</sub> [W/m]	1324	1626	1937	1439	1751	2095	1670	1996	2407
Температурный экспонент n [-]	1,2877	1,2754	1,3142	1,2898	1,2809	1,3184	1,2939	1,2920	1,3266

Вес и объем воды см. стр. 18.

Характеристическое уравнение :  $\Phi_L = K_f \cdot H^b \cdot \Delta T^{(c_0+c_1 \cdot H)}$

<b>20 °C</b>		Количество профилей i [шт.]	t <sub>1</sub> /t <sub>2</sub> [°C]	ТЕПЛОВАЯ МОЩНОСТЬ Q [Вт] СОГЛАСНО EN 442										
Тип	Высота H [мм]			Шаг подключения h [мм]	Длина L [мм]	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
						K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
				<b>1600</b>			<b>1800</b>			<b>2000</b>				
				1550			1750			1950				
				50			50			50				
Тепловая мощность Q [Вт]														
<b>144</b>	<b>2</b>	90/70	344	404	494	386	446	550	428	487	605			
		70/55	220	258	312	246	285	347	273	311	381			
		55/45	140	165	197	157	182	219	174	198	240			
<b>218</b>	<b>3</b>	90/70	521	612	748	584	676	832	648	738	915			
		70/55	332	391	472	373	431	525	413	471	577			
		55/45	212	250	298	237	275	331	263	300	364			
<b>366</b>	<b>5</b>	90/70	874	1027	1256	981	1134	1397	1088	1238	1537			
		70/55	558	656	793	626	724	882	693	791	969			
		55/45	356	419	500	398	462	556	441	504	611			
<b>514</b>	<b>7</b>	90/70	1227	1442	1764	1377	1593	1962	1528	1739	2158			
		70/55	784	922	1114	879	1017	1238	974	1110	1361			
		55/45	500	588	702	560	649	780	620	708	857			
<b>588</b>	<b>8</b>	90/70	1404	1650	2018	1576	1822	2244	1748	1990	2469			
		70/55	897	1055	1274	1005	1164	1417	1114	1270	1557			
		55/45	572	673	804	640	742	893	709	810	981			
<b>662</b>	<b>9</b>	90/70	1581	1858	2272	1774	2051	2527	1968	2240	2779			
		70/55	1009	1187	1435	1132	1310	1595	1254	1430	1753			
		55/45	644	758	905	721	836	1005	798	911	1104			
<b>884</b>	<b>12</b>	90/70	2111	2481	3033	2369	2739	3374	2628	2991	3711			
		70/55	1348	1586	1916	1511	1750	2130	1675	1910	2341			
		55/45	859	1012	1208	962	1116	1342	1066	1217	1475			
<b>958</b>	<b>13</b>	90/70	2288		3287	2567		3656	2848					
		70/55	1461		2076	1638		2308	1815					
		55/45	931		1309	1043		1454	1155					

ОСНОВНЫЕ ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ									
Тип	K10V	K11V	K20V	K10V	K11V	K20V	K10V	K11V	K20V
	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM	K10VM	K11VM	K20VM
Высота H [мм]	<b>1600</b>			<b>1800</b>			<b>2000</b>		
Номинальная тепловая мощность Q <sub>N</sub> [W/m]	1900	2234	2715	2131	2466	3019	2363	2692	3320
Температурный коэффициент n [-]	1,2966	1,2937	1,3283	1,2993	1,2955	1,3299	1,3020	1,2973	1,3316

Вес и объем воды см. стр. 18.

Характеристическое уравнение :  $\Phi_L = K_L \cdot H^b \cdot \Delta T^{(c_0+c_1 \cdot H)}$